

Ficha técnica

Latiguillo F.O. duplex, OM1 Multimodo
62,5/125 µm ST-UPC / LC-UPC



Latiguillo F.O. duplex, OM1 Multimodo 62,5/125 µm ST-UPC / LC-UPC

Referencia: 35GT2STLC2M

EAN: 8435481001420

Latiguillo F.O. duplex, OM1 Multimodo 62,5/125 µm ST-UPC / LC-UPC



Cubierta

-20 a 70 °C LSZH

Datos técnicos

Tipo conector	ST-UPC/LC-UPC
Ø externo	3 mm
Color cubierta	Naranja
Material férula	Cerámica zirconia
Tipo de fibra	Multimodo 62.5/125 µm OM1
Radio curvatura mínimo(estático)	45 mm
Estándares	IEC 60793, IEC 61754-2, IEC 61754-20, Telcordia GR-409, IEC 60332, IEC 60754, IEC 61034

CE	SI
RoHs	SI
Durabilidad	1000 conexiones
Longitud del cable	2 m
Tipo latiguillo	Duplex
Longitud de onda	850/1300 nm
Atenuación	<3.2 / <0.8 (850/1300 nm nm (dB/Km))



GTLAN Expertos en Telecomunicaciones

+34 961 366 571
comercial@gtlan.com · gtlan.com

Ficha técnica

Latiguillo F.O. duplex, OM1 Multimodo
62,5/125 ?m ST-UPC / LC-UPC

Datos logísticos

Embalaje

Unitario